

## MOTOR DATA SHEET

Motor type: **SEh80-2CF**

Series: **SINGLE PHASE**



06-06-2025

### ELECTRICAL PARAMETERS

| U   | CONN. | f  | P   |    | Duty | I   | n    | T    | TL/T | TB/T | IL/I | Efficiency at load [%] |     |      | Power factor at load [-] |     |      |
|-----|-------|----|-----|----|------|-----|------|------|------|------|------|------------------------|-----|------|--------------------------|-----|------|
| V   | -     | Hz | kW  | HP | -    | A   | rpm  | Nm   | -    | -    | -    | 2/4                    | 3/4 | 4/4  | 2/4                      | 3/4 | 4/4  |
| 230 | -     | 50 | 1.5 | 2  | S1   | 9.5 | 2800 | 5.12 | 1.9  | 1.7  | 3.7  | -                      | -   | 75.0 | -                        | -   | 0.96 |

### GENERAL DATA

|                                       |                 |                                      |           |
|---------------------------------------|-----------------|--------------------------------------|-----------|
| Efficiency class                      | -               | Sound pressure level [dB]            | -         |
| Frame size                            | 80              | Sound power level [dB]               | -         |
| Number of poles                       | 2               | Terminal box position                | top       |
| Starting method                       | DOL             | Possibility of terminal box rotation | yes       |
| Insulation class                      | F               | Bearing on D-side                    | 62042Z    |
| Frequency converter supply            | -               | Bearing on ND-side                   | 62042Z    |
| Mounting arrangement                  | IMB3/B5/B35/B14 | Bearings regreasing                  | no        |
| Cooling method                        | IC411           | Housing - material                   | aluminium |
| Weight (IMB3) [kg]                    | 12.2            | Feet - material                      | aluminium |
| Moment of inertia [kgm <sup>2</sup> ] | 0.00142         | Bearing shields - material           | aluminium |
| Direction of rotation                 | CW/CCW          | Painting                             | RAL5010   |
| Degree of protection                  | IP 54/IP 55     | Climatic execution                   | U/2       |

### ENVIRONMENTAL CONDITIONS

|                          |                    |                              |            |
|--------------------------|--------------------|------------------------------|------------|
| Ambient temperature [°C] | from -15 up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%]    | up to 95           |                              |            |

### ACCESSORY

|                                |    |                                 |           |
|--------------------------------|----|---------------------------------|-----------|
| Number of terminals or cables  | 4  | Temperature sensors in bearings | no        |
| Cable glands/inlets            | 1  | Winding heaters                 | no        |
| Temperature sensors in winding | no | Optional accessories            | on demand |

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand

### ADDITIONAL INFO

|                          |    |                               |    |
|--------------------------|----|-------------------------------|----|
| Run capacitor [mikroF/V] | 40 | Starting capacitor [mikroF/V] | 60 |
|--------------------------|----|-------------------------------|----|