

MOTOR DATA SHEET

Motor type: 3SSIE56-2BR(F)

Series: SINGLE PHASE IE3



22-10-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	F	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
230	-	50	0.12	0.17	S1	0.85	2750	0.42	1.5	1.4	2.8	-	1	60.8	-	-	0.99

GENERAL DATA						
Efficiency class	IE3	Sound pressure level [dB]	-			
Frame size	56	Sound power level [dB]	-			
Number of poles	2	Terminal box position	top			
Starting method	DOL	Possibility of terminal box rotation	no			
Insulation class	F	Bearing on D-side	62012Z			
Frequency converter supply	-	Bearing on ND-side	62012Z			
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no			
Cooling method	IC411	Housing - material	aluminium			
Weight (IMB3) [kg]	3.4	Feet - material	aluminium			
Moment of inertia [kgm2]	0.0001	Bearing shields - material	aluminium			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP 54/IP 55	Climatic execution	U/2			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	od -30 do +60	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY						
Number of terminals or cables	4	Temperature sensors in bearings	no			
Cable glands/inlets	1	Winding heaters	no			
Temperature sensors in winding	no	Optional accessories	on demand			

STANDARDS	
IEC 60034-1	

CERTIFICATES	
on demand	

ADDITIONAL INFO							
Run capacitor [mikroF/V]	10	Starting capacitor [mikroF/V]	25				

