

# MOTOR DATA SHEET

Motor type: **3SIE112M8**

Series: **IE3**



27-07-2024

## ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
			kW	HP								-	-	-	2/4	3/4	4/4
400	Δ	50	1.5	2.0	S1	3.9	700	20.5	1.7	2.0	4.6	79.2	80.8	79.7	0.47	0.60	0.70
690	Y	50	1.5	2.0	S1	2.2	700	20.5	1.7	2.0	4.6	79.2	80.8	79.7	0.47	0.60	0.70

## GENERAL DATA

Efficiency class	IE3	Sound pressure level [dB]	47
Frame size	112	Sound power level [dB]	56
Number of poles	8	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63062ZC3
Frequency converter supply	yes	Bearing on ND-side	63062ZC3
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	33.5	Feet - material	aluminium
Moment of inertia [kgm <sup>2</sup> ]	0.0168	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

## ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

## ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

## STANDARDS

IEC 60034-1

## CERTIFICATES

on demand