

MOTOR DATA SHEET

Motor type: **3SIE315M8A**

Series: **IE3**



15-06-2025

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	75	100	S1	145	739	969	2.1	2.8	6.6	93.2	93.6	93.1	0.64	0.75	0.80
690	Y	50	75	100	S1	84.2	739	969	2.1	2.8	6.6	93.2	93.6	93.1	0.64	0.75	0.80

GENERAL DATA

Efficiency class	IE3	Sound pressure level [dB]	66
Frame size	315	Sound power level [dB]	76
Number of poles	8	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6318C3
Frequency converter supply	on demand	Bearing on ND-side	6318C3
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	960	Feet - material	cast iron
Moment of inertia [kgm ²]	2.6	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	2 + 1	Winding heaters	on demand
Temperature sensors in winding	3 x PTC	Optional accessories	on demand

STANDARDS

IEC 60034-1

CERTIFICATES

on demand