



## MOTOR DATA SHEET

Motor type: **3SIE315S2**

Series: **IE3**

19-02-2026

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
			kW	HP								-	-	-	2/4	3/4	4/4
400	Δ	50	110	150	S1	181	2978	353	1.9	2.9	6.9	95.4	95.6	95.2	0.85	0.89	0.92
690	Y	50	110	150	S1	105	2978	353	1.9	2.9	6.9	95.4	95.6	95.2	0.85	0.89	0.92

### GENERAL DATA

Efficiency class	IE3	Sound pressure level [dB]	77
Frame size	315	Sound power level [dB]	87
Number of poles	2	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6315C3
Frequency converter supply	on demand	Bearing on ND-side	6315C3
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	865	Feet - material	cast iron
Moment of inertia [kgm <sup>2</sup> ]	0.98	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	2 + 1	Winding heaters	on demand
Temperature sensors in winding	3 x PTC	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand