

MOTOR DATA SHEET

Motor type: SIE200L8_4W-K



31-12-2024

Series: Multi speed

ELECTRICAL PARAMETERS																	
U	CONN.	f		P	Duty	I	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Powe	r factor at l	oad [-]
V	-	Hz	kW	HP	-	А	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	7.0	9.4	S1	14.8	735	90.9	1.8	2.3	5.2	-	-	84.5	-	-	0.81
400	YY	50	28	38	S1	54	1470	182	2.1	2.6	6.3	-	-	89.7	-	-	0.84

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	60 69			
Frame size	200	Sound power level [dB]	70 79			
Number of poles	8 4 Terminal box position		on right side			
Starting method	DOL / DOL	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	6312P63E1			
Frequency converter supply	on demand	Bearing on ND-side	6312P63E1			
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes			
Cooling method	IC411	Housing - material	cast iron			
Weight (IMB3) [kg]	255	Feet - material	cast iron			
Moment of inertia [kgm2]	0.47	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	Ν			

	ENVIRONMENTAL CONDITIONS								
Ambient temperature [°C]		up to +40	Altitude above sea level [m]	up to 1000					
	Relative humidity [%]	up to 95							

ACCESSORY							
Number of terminals or cables	6	Temperature sensors in bearings	on demand				
Cable glands/inlets	2 + 1	Winding heaters	on demand				
Temperature sensors in winding	yes	Optional accessories	on demand				

STANDARDS
IEC 60034-1

CERTIFICATES

on demand



As part of our development program, we reserve the rights to alter or amend any of the specifications without giving prior notice.

Copyright © 2024 Cantoni Group www.cantonigroup.com