



## MOTOR DATA SHEET

Motor type: **Sg112M-4\_2**

Series: **Multi speed**

22-12-2024

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
			kW	HP								-	-	-	2/4	3/4	4/4
400	Δ	50	3.3	4.50	S1	6.7	1435	21.96	2.2	2.7	6.9	83.0	84.3	83.3	0.67	0.80	0.85
400	YY	50	4.5	6.2	S1	9.0	2865	15	2.2	2.6	5.9	80.3	82.2	81.7	0.71	0.82	0.88

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	60 70
Frame size	112	Sound power level [dB]	70 74
Number of poles	4 2	Terminal box position	top
Starting method	DOL / DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63062Z
Frequency converter supply	on demand	Bearing on ND-side	63062Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	33	Feet - material	aluminium
Moment of inertia [kgm <sup>2</sup> ]	0.012	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP 55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand