



## MOTOR DATA SHEET

Motor type: **Sg132S-8\_4**

Series: **Multi speed**

22-12-2024

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
			kW	HP								-	-	-	2/4	3/4	4/4
400	Δ	50	2.5	3.4	S1	6.9	710	33.63	1.9	2.5	4.6	73.2	77.0	77.5	0.44	0.57	0.67
400	YY	50	4.2	5.8	S1	8.2	1410	28.45	1.5	2.2	5.1	83.8	83.6	81.6	0.82	0.88	0.91

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	58 66
Frame size	132	Sound power level [dB]	70 70
Number of poles	8 4	Terminal box position	top
Starting method	DOL / DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63082Z
Frequency converter supply	on demand	Bearing on ND-side	63082Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	on demand
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	61	Feet - material	cast iron
Moment of inertia [kgm <sup>2</sup> ]	0.0319	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP 55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand