



MOTOR DATA SHEET

Motor type: **Sg160L-6_4**

Series: **Multi speed**

22-12-2024

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
			kW	HP								-	-	-	2/4	3/4	4/4
400	Y	50	7.0	9.4	S1	15	970	68.92	2.3	2.9	7.3	83.0	85.0	85.0	0.58	0.71	0.79
400	Y	50	10.8	14.7	S1	20.4	1450	71.13	1.9	2.8	7.2	85.1	86.9	86.8	0.74	0.84	0.88

GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	66 67
Frame size	160	Sound power level [dB]	69 77
Number of poles	6 4	Terminal box position	top
Starting method	DOL / DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63092Z
Frequency converter supply	on demand	Bearing on ND-side	63092Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	on demand
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	135	Feet - material	cast iron
Moment of inertia [kgm ²]	0.097	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP 55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

STANDARDS

IEC 60034-1

CERTIFICATES

on demand