



## MOTOR DATA SHEET

Motor type: **Sg160M-8\_6\_4**

Series: **Multi speed**

22-12-2024

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
			kW	HP								-	-	-	2/4	3/4	4/4
400	Δ	50	3.5	4.8	S1	9.6	725	46.1	1.8	2.6	5.4	74.6	78.7	79.8	0.44	0.57	0.66
400	Y	50	4.6	6.3	S1	10.7	975	45.06	1.5	2.5	5.8	78.4	81.6	82.3	0.53	0.66	0.75
400	YY	50	6.4	8.6	S1	12	1435	42.59	1.5	2.0	5.9	85.2	85.3	83.5	0.84	0.90	0.92

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	67 67 70
Frame size	160	Sound power level [dB]	62 62 60
Number of poles	8 6 4	Terminal box position	top
Starting method	DOL / DOL / DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63092Z
Frequency converter supply	on demand	Bearing on ND-side	63092Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	on demand
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	105	Feet - material	cast iron
Moment of inertia [kgm <sup>2</sup> ]	0.07	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP 55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand