

MOTOR DATA SHEET



15-06-2025

Motor type: ESg213T-8

Series: NEMA Epact

ELECTRICAL PARAMETERS																	
U	CONN.	f	ŀ	D	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at lo	oad [-]
V	-	Hz	kW	HP	-	А	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
460		60	1.5	2	cont.	3.2	875		2.3	3.4	6.3	78.3	81.7	82.5			

GENERAL DATA						
Efficiency class	NEMA EPACT	Frame size	213			
Number of poles	8	Insulation class	F			
Frequency converter supply	on demand	Cooling method	IC411			
Direction of rotation	CW/CCW	Painting	RAL5010			
Climatic execution	N					

ENVIRONMENTAL CONDITIONS						
Ambient temperature [°C]	up to +40 Altitude above sea level [m]		up to 1000			
Relative humidity [%]	up to 95					

ACCESSORY							
Optional accessories	on demand						
STANDARDS							
NEMA MG-1							
CERTIFICATES							

CSA

ADDITIONAL INFO						
NEMA code letter	К					

As part of our development program, we reserve the rights to alter or amend any of the specifications without giving prior notice.



