



## MOTOR DATA SHEET

Motor type: **dSg160L4-EP**

Series: **General purpose**

28-12-2024

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
1000	Y	50	15	20	S1	11.2	1460	98	2.5	3.2	7.9	89.9	90.5	89.8	0.72	0.82	0.86

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	68
Frame size	160	Sound power level [dB]	78
Number of poles	4	Terminal box position	top
Starting method	DOL	Possibility of terminal box rotation	no
Insulation class	F	Bearing on D-side	63092Z
Frequency converter supply	on demand	Bearing on ND-side	63092Z
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	no
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	170	Feet - material	cast iron
Moment of inertia [kgm <sup>2</sup> ]	0.08	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 100		

### ACCESSORY

Number of terminals or cables	3	Temperature sensors in bearings	1 x bimetal (D-side)
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	3 x bimetallic	Optional accessories	on demand

### STANDARDS

IEC 60034-1, IEC 60079-0, IEC 60079-1

### CERTIFICATES

ATEX, EAC, BiH

### ADDITIONAL INFO

Ex marking	I M2 Ex db I Mb / II2G Ex db IIA T5 Gb	
------------	--	--