



MOTOR DATA SHEET

Motor type: **ExSg132S-6-2GT4_2D**

Series: **Gas and Dust - category 2D, 3D, 3G**

27-09-2024

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	2.2	3	S1	5.1	960	21.9	2.3	3	7.7	77.6	80.4	80.7	0.57	0.70	0.78

GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	62
Frame size	132	Sound power level [dB]	73
Number of poles	6	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63082Z
Frequency converter supply	no	Bearing on ND-side	63082Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight [kg]	52	Feet - material	cast iron
Moment of inertia [kgm ²]	0.024	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP66	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	2	Winding heaters	on demand
Temperature sensors in winding	3 x PTC	Optional accessories	on demand

STANDARDS

EN 60034-1, EN 60079-0, EN 60079-7, EN 60079-15, EN 60079-31

CERTIFICATES

ATEX

ADDITIONAL INFO

Ex marking	II 2G Ex eb IIC T4 Gb / II 2D Ex tb IIIC T125°C Db	
------------	---	--