



MOTOR DATA SHEET

Motor type: **Sg132M-12B**

Series: **ABOVE 8-POLES**

15-06-2025

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	2.2	3.0	S1	8.1	460	45.67	1.2	1.8	3.0	68.5	69.2	70.2	0.45	0.49	0.56
690	Y	50	2.2	3.0	S1	4.7	460	45.67	1.2	1.8	3.0	68.5	69.2	70.2	0.45	0.49	0.56

GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	73
Frame size	132	Sound power level [dB]	62
Number of poles	12	Terminal box position	top
Starting method	DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6308 2Z C3
Frequency converter supply	yes	Bearing on ND-side	6308 2Z C3
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	72	Feet - material	cast iron
Moment of inertia [kgm ²]	0.04	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

STANDARDS

IEC 60034-1

CERTIFICATES

on demand