



MOTOR DATA SHEET

Motor type: **ExSg132M-6A-2GT3**

Series: **INCREASED SAFETY**

27-09-2024

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	4	5.5	S1	8.5	950	40.2	2.3	2.9	7	81.9	83.4	82.9	0.64	0.76	0.82

GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	62
Frame size	132	Sound power level [dB]	73
Number of poles	6	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63082Z
Frequency converter supply	no	Bearing on ND-side	63082Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight [kg]	64	Feet - material	cast iron
Moment of inertia [kgm ²]	0.032	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	2	Winding heaters	no
Temperature sensors in winding	on demand	Optional accessories	on demand

STANDARDS

EN 60079-0, EN 60079-15

CERTIFICATES

ATEX

ADDITIONAL INFO

tE heating time up to T3 temperature [s]	14	Ex marking	II 2G Ex eb IIC T3
------------------------------------------	----	------------	--------------------