



MOTOR DATA SHEET

Motor type: **(E)cSg160L6-EP**

Series: **FLAMEPROOF IE1**

27-09-2024

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	11	15	S1	22	960	109	2.2	2.8	6.7	88.3	88.9	88.2	0.67	0.78	0.82

GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	57
Frame size	160	Sound power level [dB]	67
Number of poles	6	Terminal box position	top
Starting method	DOL	Possibility of terminal box rotation	no
Insulation class	F	Bearing on D-side	63092Z
Frequency converter supply	on request - execution (-f)	Bearing on ND-side	63092Z
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	no
Cooling method	IC411	Housing - material	cast iron
Weight [kg]	173	Feet - material	cast iron
Moment of inertia [kgm ²]	0.1	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 100		

ACCESSORY

Number of terminals or cables	3	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

STANDARDS

IEC 60034-1, IEC 60079-0, IEC 60079-1, IEC 60079-7

CERTIFICATES

ATEX, EAC, BiH

ADDITIONAL INFO

Ex marking	II 2G Ex db (eb) IIB Tb Gb	
------------	----------------------------	--