



MOTOR DATA SHEET

Motor type: **Ex2SIE_71-4B**

Series: **INCREASED SAFETY IE3**

27-09-2024

ELECTRICAL PARAMETERS

| U | CONN. | f | P | | Duty | I | n | T | TL/T | TB/T | IL/I | Efficiency at load [%] | | | Power factor at load [-] | | |
|-----|-------|----|------|------|------|------|------|------|------|------|------|------------------------|---|------|--------------------------|-----|------|
| | | | kW | HP | | | | | | | | - | - | - | 2/4 | 3/4 | 4/4 |
| 400 | Y | 50 | 0.37 | 0.50 | S1 | 1.15 | 1410 | 2.51 | 2.9 | 3.1 | 4.1 | - | - | 72.7 | - | - | 0.64 |

GENERAL DATA

| | | | |
|---------------------------------------|-----------------|--------------------------------------|-----------|
| Efficiency class | IE2 | Sound pressure level [dB] | - |
| Frame size | 71 | Sound power level [dB] | - |
| Number of poles | 4 | Terminal box position | top |
| Starting method | DOL | Possibility of terminal box rotation | no |
| Insulation class | F | Bearing on D-side | 6203 2Z |
| Frequency converter supply | no | Bearing on ND-side | 6203 2Z |
| Mounting arrangement | IMB3/B5/B35/B14 | Bearings regreasing | no |
| Cooling method | IC411 | Housing - material | aluminium |
| Weight (IMB3) [kg] | 8.1 | Feet - material | aluminium |
| Moment of inertia [kgm ²] | - | Bearing shields - material | aluminium |
| Direction of rotation | CW/CCW | Painting | RAL5010 |
| Degree of protection | IP66 | Climatic execution | NU/2 |

ENVIRONMENTAL CONDITIONS

| | | | |
|--------------------------|--------------------|------------------------------|------------|
| Ambient temperature [°C] | from -20 up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%] | up to 95 | | |

ACCESSORY

| | | | |
|--------------------------------|-----------|---------------------------------|----|
| Number of terminals or cables | 6 | Temperature sensors in bearings | no |
| Cable glands/inlets | 2 | Winding heaters | no |
| Temperature sensors in winding | on demand | Optional accessories | no |

STANDARDS

PN-EN 60079-7:2016

CERTIFICATES

ATEX

ADDITIONAL INFO

| | | | |
|--|---------------------------|--|----|
| tE heating time up to T3 temperature [s] | 34 | tE heating time up to T4 temperature [s] | 13 |
| Ex marking | Ex II 2 G Ex eb IIC Tx Gb | | |