

# MOTOR DATA SHEET

Motor type: **3SIE355H6C**

Series: **IE3**



22-12-2024

## ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
			kW	HP								-	-	-	2/4	3/4	4/4
400	Δ	50	315	425	S1	558	991	3036	2.0	2.2	7.1	95.5	95.8	95.8	0.74	0.83	0.85
690	Y	50	315	425	S1	322	991	3036	2.0	2.2	7.1	95.5	95.8	95.8	0.74	0.83	0.85

## GENERAL DATA

Efficiency class	IE3	Sound pressure level [dB]	78
Frame size	355	Sound power level [dB]	-
Number of poles	6	Terminal box position	top/* side of housing
Starting method	DOL, Y/Δ or VSD	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6322 C3
Frequency converter supply	yes	Bearing on ND-side	6322 C3
Mounting arrangement	IMB3/B35/V1*	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	2390	Feet - material	cast iron
Moment of inertia [kgm <sup>2</sup> ]	12.7	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

## ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

## ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	2 x Pt100 (1 pc/bearing)
Cable glands/inlets	2	Winding heaters	on demand
Temperature sensors in winding	6 x Pt100 (2pcs./phase)	Optional accessories	on demand

## STANDARDS

IEC 60034-1

## CERTIFICATES

on demand