

MOTOR DATA SHEET

Motor type: **3SIE355ML4A**

Series: **IE3**



22-11-2024

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
			kW	HP								-	-	-	2/4	3/4	4/4
400	Δ	50	250	355	S1	422	1489	1603	2.0	2.3	7.4	95.8	96.1	96.0	0.79	0.86	0.89
690	Y	50	250	355	S1	244	1489	1603	2.0	2.3	7.4	95.8	96.1	96.0	0.79	0.86	0.89

GENERAL DATA

Efficiency class	IE3	Sound pressure level [dB]	78
Frame size	355	Sound power level [dB]	-
Number of poles	4	Terminal box position	top/* side of housing
Starting method	DOL, Y/Δ or VSD	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6222 C3/* 6322 C3
Frequency converter supply	yes	Bearing on ND-side	6222 C3/* 6322 C3
Mounting arrangement	IMB3/B35/V1*	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Feet - material	cast iron	Moment of inertia [kgm ²]	5.3
Bearing shields - material	cast iron	Direction of rotation	CW/CCW
Painting	RAL5010	Degree of protection	IP55
Climatic execution	N		

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	2	Winding heaters	on demand
Temperature sensors in winding	3 x PTC (1pc/phase)	Optional accessories	on demand

STANDARDS

IEC 60034-1

CERTIFICATES

on demand