

# MOTOR DATA SHEET

Motor type: **3SIE400H2F**

Series: **IE3**



19-02-2026

## ELECTRICAL PARAMETERS

| U   | CONN.  | f  | P   |     | Duty | I    | n    | T    | TL/T | TB/T | IL/I | Efficiency at load [%] |      |      | Power factor at load [-] |      |      |
|-----|--------|----|-----|-----|------|------|------|------|------|------|------|------------------------|------|------|--------------------------|------|------|
| V   | -      | Hz | kW  | HP  | -    | A    | rpm  | Nm   | -    | -    | -    | 2/4                    | 3/4  | 4/4  | 2/4                      | 3/4  | 4/4  |
| 400 | Δ or Y | 50 | 630 | 850 | S1   | 1049 | 2985 | 2016 | 1.5  | 2.8  | 7.9  | 95.4                   | 96.2 | 96.3 | 0.84                     | 0.89 | 0.90 |
| 690 | Δ or Y | 50 | 630 | 850 | S1   | 606  | 2985 | 2016 | 1.5  | 2.8  | 7.9  | 95.4                   | 96.2 | 96.3 | 0.84                     | 0.89 | 0.90 |

## GENERAL DATA

|                                       |                          |                                      |           |
|---------------------------------------|--------------------------|--------------------------------------|-----------|
| Efficiency class                      | IE3                      | Sound pressure level [dB]            | 84        |
| Frame size                            | 400                      | Sound power level [dB]               | -         |
| Number of poles                       | 2                        | Terminal box position                | top       |
| Starting method                       | bezpośredni. Y/D lub VSD | Possibility of terminal box rotation | yes       |
| Insulation class                      | F                        | Bearing on D-side                    | 6218 C3   |
| Frequency converter supply            | yes                      | Bearing on ND-side                   | 6218 C3   |
| Mounting arrangement                  | IMB3/B35                 | Bearings regreasing                  | yes       |
| Cooling method                        | IC411                    | Housing - material                   | cast iron |
| Weight (IMB3) [kg]                    | 3100                     | Feet - material                      | cast iron |
| Moment of inertia [kgm <sup>2</sup> ] | 8.7                      | Bearing shields - material           | cast iron |
| Direction of rotation                 | according to the order   | Painting                             | RAL5010   |
| Degree of protection                  | IP55                     | Climatic execution                   | N         |

## ENVIRONMENTAL CONDITIONS

|                          |           |                              |            |
|--------------------------|-----------|------------------------------|------------|
| Ambient temperature [°C] | up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%]    | up to 95  |                              |            |

## ACCESSORY

|                                |                         |                                 |                          |
|--------------------------------|-------------------------|---------------------------------|--------------------------|
| Number of terminals or cables  | 6                       | Temperature sensors in bearings | 2 x Pt100 (1 pc/bearing) |
| Cable glands/inlets            | 2                       | Winding heaters                 | on demand                |
| Temperature sensors in winding | 6 x Pt100 (2pcs./phase) | Optional accessories            | on demand                |

## STANDARDS

IEC 60034-1

## CERTIFICATES

on demand