



since 1921

MOTOR DATA SHEET

Motor type: **3SIE450H4C**Series: **IE3**

22-11-2024

ELECTRICAL PARAMETERS

| U | CONN. | f | P | | Duty | I | n | T | TL/T | TB/T | IL/I | Efficiency at load [%] | | | Power factor at load [-] | | |
|-----|--------|----|-----|------|------|-----|------|------|------|------|------|------------------------|------|------|--------------------------|------|------|
| V | - | Hz | kW | HP | - | A | rpm | Nm | - | - | - | 2/4 | 3/4 | 4/4 | 2/4 | 3/4 | 4/4 |
| 690 | Δ or Y | 50 | 800 | 1070 | S1 | 788 | 1493 | 5117 | 1.6 | 2.6 | 6.8 | 96.0 | 96.5 | 96.5 | 0.79 | 0.86 | 0.88 |

GENERAL DATA

| | | | |
|----------------------------|---------------|---------------------------------------|------------------------|
| Efficiency class | IE3 | Sound pressure level [dB] | 84 |
| Frame size | 450 | Sound power level [dB] | - |
| Number of poles | 4 | Terminal box position | top/ * side |
| Starting method | direct or VSD | Possibility of terminal box rotation | yes |
| Insulation class | F | Bearing on D-side | 6324 C3 |
| Frequency converter supply | yes | Bearing on ND-side | NU222 /* 7322 BTVP |
| Mounting arrangement | IMB3/B35/V1* | Bearings regreasing | yes |
| Cooling method | IC411 | Housing - material | cast iron |
| Feet - material | cast iron | Moment of inertia [kgm ²] | 31.6 |
| Bearing shields - material | cast iron | Direction of rotation | according to the order |
| Painting | RAL5010 | Degree of protection | IP55 |
| Climatic execution | N | | |

ENVIRONMENTAL CONDITIONS

| | | | |
|--------------------------|-----------|------------------------------|------------|
| Ambient temperature [°C] | up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%] | up to 95 | | |

ACCESSORY

| | | | |
|--------------------------------|-------------------------|---------------------------------|--------------------------|
| Number of terminals or cables | 3 | Temperature sensors in bearings | 2 x Pt100 (1 pc/bearing) |
| Cable glands/inlets | 3 | Winding heaters | on demand |
| Temperature sensors in winding | 6 x Pt100 (2pcs./phase) | Optional accessories | on demand |

STANDARDS

IEC 60034-1

CERTIFICATES

on demand