

MOTOR DATA SHEET

Motor type: Sh90S-10



15-01-2025

Series: ABOVE 8-POLES

	ELECTRICAL PARAMETERS																
U	CONN.	f	I	P	Duty	I	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	А	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
230	Δ	50	0.25	0.34	S1	2.21	560	4.26	1.8	2.0	2.2	44.9	51.3	55.6	0.38	0.46	0.51
400	Y	50	0.25	0.34	S1	1.27	560	4.26	1.8	2.0	2.2	44.9	51.3	55.6	0.38	0.46	0.51

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	63			
Frame size	90	Sound power level [dB]	53			
Number of poles	10 Terminal box position		top			
Starting method	DOL	Possibility of terminal box rotation	yes			
Insulation class	F Bearing on D-side		6205 2Z C3			
Frequency converter supply	yes	Bearing on ND-side	6205 2Z C3			
Mounting arrangement	IMB3/B5/B35/B14 Bearings regreasing		no			
Cooling method	IC411	Housing - material	aluminium			
Weight (IMB3) [kg]	17	Feet - material	aluminium			
Moment of inertia [kgm2]	0.0028	Bearing shields - material	aluminium			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	Ν			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY						
Number of terminals or cables	6	Temperature sensors in bearings	on demand			
Cable glands/inlets	1	Winding heaters	on demand			
Temperature sensors in winding	on demand	Optional accessories	on demand			

STANDARDS
IEC 60034-1

CERTIFICATES

on demand



As part of our development program, we reserve the rights to alter or amend any of the specifications without giving prior notice.

Copyright © 2025 Cantoni Group www.cantonigroup.com