



MOTOR DATA SHEET

Motor type: **(E)cSTe(b)160L8-IE3**

Series: **FLAMEPROOF IE3**

01-09-2024

| ELECTRICAL PARAMETERS | | | | | | | | | | | | | | | | | |
|-----------------------|-------|----|-----|----|------|------|-----|-----|------|------|------|------------------------|------|------|--------------------------|------|------|
| U | CONN. | f | P | | Duty | I | n | T | TL/T | TB/T | IL/I | Efficiency at load [%] | | | Power factor at load [-] | | |
| V | - | Hz | kW | HP | - | A | rpm | Nm | - | - | - | 2/4 | 3/4 | 4/4 | 2/4 | 3/4 | 4/4 |
| 400 | Y | 50 | 7.5 | 10 | S1 | 16.1 | 710 | 101 | 2.0 | 2.6 | 5.4 | 87.9 | 88.5 | 87.3 | 0.60 | 0.71 | 0.77 |

| GENERAL DATA | | | |
|---------------------------------------|-------------|--------------------------------------|------------|
| Efficiency class | IE3 | Sound pressure level [dB] | - |
| Frame size | 160 | Sound power level [dB] | - |
| Number of poles | 8 | Terminal box position | top |
| Starting method | DOL | Possibility of terminal box rotation | yes |
| Insulation class | F | Bearing on D-side | 6309 2Z C3 |
| Frequency converter supply | on demand | Bearing on ND-side | 6309 2Z C3 |
| Mounting arrangement | IMB3/B5/B35 | Bearings regreasing | on demand |
| Cooling method | IC411 | Housing - material | cast iron |
| Weight (IMB3) [kg] | 240 | Feet - material | cast iron |
| Moment of inertia [kgm ²] | 0.102 | Bearing shields - material | cast iron |
| Direction of rotation | CW/CCW | Painting | RAL5010 |
| Degree of protection | IP55 | Climatic execution | N |

| ENVIRONMENTAL CONDITIONS | | | |
|--------------------------|--------------------|------------------------------|------------|
| Ambient temperature [°C] | from -20 up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%] | up to 95 | | |

| ACCESSORY | | | |
|--------------------------------|-----------|---------------------------------|-----------|
| Number of terminals or cables | 3 | Temperature sensors in bearings | on demand |
| Cable glands/inlets | 1 | Winding heaters | on demand |
| Temperature sensors in winding | on demand | Optional accessories | on demand |

| STANDARDS | |
|--|--|
| IEC 60034-1, IEC 60079-0, IEC 60079-1, IEC 60079-7 | |

| CERTIFICATES | |
|----------------|--|
| ATEX, EAC, BiH | |

| ADDITIONAL INFO | |
|-----------------|---|
| Ex marking | II 2G Ex db (eb) IIB T5 Gb lub na życzenie II 2G Ex db (eb) IIC T5 Gb |